

ZR125KC-TFD

HCFC, R-22, 50Hz, 3- Phase, 380/420 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65 / 115	65 / 85
Capacity (Btu/hr)	106000	124000
Power (Watts):	9000	6300
Current (Amps):	15.80	12.30
EER (Btu/Wh):	11.80	19.70
Mass Flow (lbs/hr):	1550	1600
Sound Power (dBA):	75 Avg	80 Max
Vibration (mils(peak-)	3.0 Avg	4.5 Max
Record Date:	2006-02-13	

Mechanical

Number of Cylinders:	0	Displ(in^3/Rev):	10.20
Bore Size(in):	0.00	Displ(ft^3/hr):	1026.88
Stroke(in):	0.00		
Overall Length (in):	10.38	Mounting Length (in):	7.50
Overall Width (in):	11.23	Mounting Width (in):	7.50
Overall Height (in):	21.00	Mounting Height (in):	21.75 *
Suction Size (in):	1 3/8 Stub		
Discharge Size (in):	7/8 Stub		
Oil Recharge (oz):	106		
Initial Oil Charge (oz):	110		
Net Weight (lbs):	135		
Internal Free Volume (in^3):	809.0		
Horse Power:	10		
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	118.0	MCC (Amps):	26.9	UL File No:	SA-2337
LRA-Half Winding:		RPM:		UL File Date:	27-Sep-1996
LRA Low*:	110.0	Max Operating Current:	19.6		
RLA(=MCC/1.4;use for contactor selection):			19.2		
RLA(=MCC/1.56;use for breaker & wire size			17.2		
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	60	3	460	Air Conditioning

LineID:COPELAND.EMERSON
TEL:085-440-0736