ZR125KCE-TFD

HFC, R-407C, 50Hz, 3- Phase, 380/420 V
Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/SubCool(°F)	65 / 15	65 / 15
Capacity (Btu/hr)	103000	124500
Power (Watts):	8950	6170
Current (Amps):	16.00	12.45
EER (Btu/Wh):	11.60	20.20
Mass Flow (lbs/hr):	1500	1545
Sound Power (dBA):	74 Avg	79 Max
Vibration (mils(peak-	3.0 Avg	4.5 Max
Record Date:	2007-12-06	

Mechanical

Number of Cylinders:	0	Displ(in^3/Rev):	10.20
Bore Size(in):	0.00	Displ(ft^3/hr):	1026.88
Stroke(in):	0.00		
Overall Length (in):	10.38	Mounting Length (in):	7.50
Overall Width (in):	11.23	Mounting Width (in):	7.50
Overall Height (in):	21.00	Mounting Height (in):	21.75 *

Suction Size (in):	1 3/8 Stub
Discharge Size (in):	7/8 Stub
Oil Recharge (oz):	106
Initial Oil Charge (oz):	110
Net Weight (lbs):	135
Internal Free Volume (in^3):	809.0
Horse Power:	10

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA-High*:	118.0	MCC (Amps):	26.9	UL File No:	SA-2337
LRA-Half Winding:		RPM:		UL File Date:	27-Sep-1996
LRA Low*:	110.0	Max Operating Current:	19.6		
RLA(=MCC/1.4;use for contactor selection):		19.2			
RLA(=MCC/1.56;use for breaker & wire size		17.2			

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-134a HFC	60	3	460	Air Conditioning
R-407C HFC	60	3	460	Air Conditioning
R-134a HFC	50	3	380/420	Air Conditioning

LineID:COPELAND.EMERSON
TEL:085-440-0736

Copyright © 2010 Emerson Climate Technologies, Inc. All rights reserved.