

**ZR34K3-PFJ**

HCFC, R-22, 50Hz, 1- Phase, 220/240 V

Air Conditioning



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

**Performance**

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65 / 115	65 / 85
Capacity (Btu/hr)	28100	33300
Power (Watts):	2550	1730
Current (Amps):	12.10	8.50
EER (Btu/Wh):	11.00	19.20
Mass Flow (lbs/hr):	411	430
Sound Power (dBA):	68 Avg	73 Max
Vibration (mils(peak- Record Date:	2.0 Avg	3.0 Max
	2001-09-13	

**Mechanical**

Number of Cylinders:	0	Displ(in <sup>3</sup> /Rev):	2.82
Bore Size(in):	0.00	Displ(ft <sup>3</sup> /hr):	283.55
Stroke(in):	0.00		
Overall Length (in):	9.57	Mounting Length (in):	7.50
Overall Width (in):	9.57	Mounting Width (in):	7.50
Overall Height (in):	15.73	Mounting Height (in):	12.97 *
Suction Size (in):		3/4 Stub	
Discharge Size (in):		1/2 Stub	
Oil Recharge (oz):		38	
Initial Oil Charge (oz):		42	
Net Weight (lbs):		63	
Internal Free Volume (in <sup>3</sup> ):		161.0	
Horse Power:		3	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

**Electrical**

LRA-High*:	76.0	MCC (Amps):	19.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:		UL File Date:	14-Jun-1994
LRA Low*:	70.0	Max Operating Current:	15.3		
RLA(=MCC/1.4;use for contactor selection):		13.6			
RLA(=MCC/1.56;use for breaker & wire size		12.2			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

**Alternate Applications**

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	60	1	265	Air Conditioning

LineID:COPELAND.EMERSON  
TEL:085-440-0736