

**ZR47K3-PFJ**

HCFC, R-22, 50Hz, 1- Phase, 220/240 V

Air Conditioning



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

**Performance**

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65 / 115	65 / 85
Capacity (Btu/hr)	39400	46500
Power (Watts):	3460	2420
Current (Amps):	16.80	12.60
EER (Btu/Wh):	11.40	19.20
Mass Flow (lbs/hr):	575	600
Sound Power (dBA):	68 Avg	73 Max
Vibration (mils(peak- Record Date:	2.0 Avg 2001-09-13	3.0 Max

**Mechanical**

Number of Cylinders:	0	Displ(in^3/Rev):	3.86
Bore Size(in):	0.00	Displ(ft^3/hr):	389.08
Stroke(in):	0.00		
Overall Length (in):	9.69	Mounting Length (in):	7.50
Overall Width (in):	9.69	Mounting Width (in):	7.50
Overall Height (in):	16.95	Mounting Height (in):	17.18 *
Suction Size (in):	7/8 Stub		
Discharge Size (in):	1/2 Stub		
Oil Recharge (oz):	38		
Initial Oil Charge (oz):	42		
Net Weight (lbs):	69		
Internal Free Volume (in^3):	205.0		
Horse Power:	4		
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

**Electrical**

LRA-High*:	114.0	MCC (Amps):	27.0	UL File No:	
LRA-Half Winding:		RPM:		UL File Date:	14-Jun-1994
LRA Low*:	105.0	Max Operating Current:	22.7		
RLA(=MCC/1.4;use for contactor selection):		19.3			
RLA(=MCC/1.56;use for breaker & wire size		17.3			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

**Alternate Applications**

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	60	1	265	Air Conditioning

LineID:COPELAND.EMERSON  
TEL:085-440-0736